

process adaption and accessories

process adaption

features

- dead space- and elastomer free process adaption for temperature sensor WTR150, WTR350 WTR450, level switch NGS150, level rod probes NST150, NST250, ...
- modulare process connection system
- hygienical compatible mounting in cases and pipelines in all areas of the food and pharma industry
- EHEDG and FDA-conform
- material 1.4404 (316L), other materials on request
- on request deliverable with material certificates

assembly advice

Important: use only welded sleeves of company promesstec, to reach a secure and optimal measuring point.
Pay attention to the max. acceptable clamping torque at assembly.

process connection for G1/2" sealing system

G 1/2						
designation	milk pipe screwing (box nut see MRÜ...)	milk pipe screwing box nut DIN11851	adapter sleeve Varivent DN50	DRD-flange (proof disk see DRA 150/950)	DRD-flange proof disk	DRD-flange flat gasket
type	MRV 150	MRÜ 150/950	VAV 150	DRD 150	DRA 150/950	DRF 150/950
dimensions	Ø DN25 Ø DN32 Ø DN40 Ø DN50 Ø DN65 Ø DN80	Ø DN25 Ø DN32 Ø DN40 Ø DN50 Ø DN65 Ø DN80	Ø DN50	Ø DN65		

process connection for G1" sealing system

G 1						
designation	milk pipe screwing (box nut see MRÜ...)	milk pipe screwing box nut DIN11851	adapter sleeve Varivent DN50	DRD-flange (proof disk see DRA 150/950)	DRD-flange proof disk	DRD-flange flat gasket
type	MRV 950	MRÜ 150/950	VAV 950	DRD 950	DRA 150/950	DRF 150/950
dimensions	Ø DN40 Ø DN50 Ø DN65 Ø DN80	Ø DN40 Ø DN50 Ø DN65 Ø DN80	Ø DN50	Ø DN65		